

# BLAM



**Depureco Industrial Vacuums USA**

19121 Marketplace Avenue, Building 1, Suite 165  
Plum Creek Business Park • Kyle • TX 78640

[www.depurecousa.com](http://www.depurecousa.com)  
[info@depurecousa.com](mailto:info@depurecousa.com)



2 HP  
**POWER**

2325 in<sup>2</sup>  
**FILTER**

11 gal  
**CAPACITY**

**SEALED MOTOR HEAD  
FROM EXTERNAL  
AGENTS**



**BRUSHLESS MOTOR**  
120 V



**H13 CLASS  
ANTISTATIC  
CARTRIDGE FILTER**



**PRESSURE GAUGE**

Dirty filter indicator.

Patented inlet  
connection with  
immersion nozzle

Double oil  
mist filter

Immersion nozzle

Nylon filter

Metal grid  
basket

Suppression  
security valve

**STAINLESS STEEL BIN WITH  
INERTIZATION BATH**  
**AISI 304**



**INLET  
WITH DEFLECTOR Ø 2.75 in**


**ALL COMPONENTS  
ARE GROUNDED**




**11gal**

**HIGHLY TRANSPORTABLE**

**COMPLIANT TO**



21 in



24 in

51 in



**Weight: 99 lbs**



# SPEC SHEET

|                             |
|-----------------------------|
| Suction type                |
| Power                       |
| Voltage   Frequency         |
| Maximum vacuum              |
| Maximum air flow            |
| Inlet                       |
| Noise level - (EN ISO 3744) |
| Bin capacity                |
| Dimensions                  |
| Height                      |
| Weight                      |
| Primary filter              |
| Type                        |
| Surface area                |
| (Class EN 60335-2-69)       |
| Media                       |

Units

HP  
V/Hz  
inH2O  
CFM  
Ø in  
dB(A)  
gal  
in  
in  
lb

BL 45 JC

|                 |
|-----------------|
| Brushless motor |
| 2   1~          |
| 120   60        |
| 92              |
| 129             |
| 2.75            |
| 72              |
| 11              |
| 21 x 20         |
| 51              |
| 99              |

in² | in

|                      |
|----------------------|
| Cartridge            |
| 2325                 |
| H13 Class            |
| Antistatic polyester |

# NORMATIVE REFERENCES

COMPLIANT TO

- NFPA 660
- NFPA 79
- UL 2011
- UL 508A
- CSA C22.2

# ACCESSORIES



ATEX STARTER KIT Ø 2.75 in



ATEX KIT PRO Ø 2.75 in